



### Batteries

Only SPEED HOUSE 800HV AAA Ni-MH (71998) are permitted

### Motor RPM Restrictions

Motors exceeding RPM Restrictions are not allowed

● **Brushless Motor**  
KV Rating is measured with X-Speed Mini-Z Motor Checker (MZW124) connected to DC6V

**Maximum KV rating**  
MZ705(Blue)/MZ605: 6400KV  
MZ706(Green)/MZ606: 4700KV

\*Motors that have ever been opened or modified in any way are not allowed. Must be factory default condition.

# 2024 Mini-Z Cup USA Regulation

Same as Japan but only Narrow and Wide Touring. Have fun with Mini-Z cup Rules.

| Class/Qualification    | Shasis *5 *6                              | Body   | Battery  | Motor & Gear   | Transmitter                                   | Tire & Wheel   |
|------------------------|---|--|--|--|---|--|
| <b>N/TOURING CLASS</b> | ↑<br>MR-03VE PRO / EVO<br>MR-04EVO2<br>*1 | ↑<br>Specified body only:<br>Bodies listed below | ↑<br>SPEED HOUSE 800HV<br>AAA Ni-MH (71998)<br>are permitted | ↑<br>MZ606/MZ706→7T X 44T<br>*Motor RPM adjustment by<br>ICS is prohibited | ↑<br>Mini-Z Certified<br>Transmitters only *4 | ↑<br>Kyosho Brand Tires only.<br>*Tire diameter must be between<br>23mm to 24.7mm except<br>for MZW40 series tires.<br>*2 *3 |
| <b>W/TOURING CLASS</b> | ↓   | ↓  | ↓  | ↓<br>MZ605/MZ705→8T X 44T<br>*Motor RPM adjustment by<br>ICS is prohibited | ↓   | ↓  |

| Class Specified Body List   |  |
|-----------------------------|--|
| <b>Narrow Touring Class</b> | <ul style="list-style-type: none"> <li>● Fairlady Z (Z33) Nismo S-tune</li> <li>● Skyline GT-R (R32/R33/R34/R35)</li> <li>● Skyline 2000GT-R (KPGC10)</li> <li>● Fairlady 240ZG</li> <li>● Silvia S13/S15</li> </ul> |
| <b>Wide Touring Class</b>   | <ul style="list-style-type: none"> <li>● SC430</li> <li>● NSX</li> <li>● NSX Concept GT</li> <li>● HSV-010</li> </ul>  |

\*1 Narrow Touring Class. Chassis needs to be MR03/MR04 Narrow RM/MM/MM2 HM. Width below 70mm. MML mount and LM Diff shaft not allowed.

\*2 Cutting and shaving tires is not allowed. Tires can be mounted on wheels with double sided tape. Tape thickness must be similar to R246-1041/1042 can only apply one round. Tire diameter is measured at the smallest spot on the front and largest spot on the rear.

\*3 No chemicals allowed on tires.

\*4 Kyosho KT432PT, EX5UR, EX6R, KT531P, NB4, NB4+, 4PM. 4PM Plus, EX10, EX-1, EX-RR, EXLTD, EXNEXT, MC8, 7PX, 7PXR, 7XC, T10PX

\*5 No additional parts or weights allowed

\*6 No modification to the board. Must be stock board for that chassis